

“Stay Connected” with



HEYware Products




a PennEngineering® Company



Heyco® Self-Closing Braided Sleeving

| MAXIMUM DIAMETER | | PART NO. Black | DESCRIPTION | PART DIMENSIONS | | | | INSTALLATION TOOL Part No. |
|------------------|------|-------------------|-----------------|------------------|------|-----------|------|-------------------------------|
| in. | mm | | | Nominal Diameter | | Spool Qty | | |
| | | | | in. | mm | ft. | m | |
| .28 | 7,0 | 8880 | SCBS-250 BLACK | .25 | 6,4 | 100 | 30,5 | 8889 |
| .39 | 10,0 | 8881 | SCBS-375 BLACK | .38 | 9,7 | | | |
| .55 | 14,0 | 8882 | SCBS-500 BLACK | .50 | 12,7 | 100 | 30,5 | 8890 |
| .67 | 17,0 | 8883 | SCBS-625 BLACK | .63 | 16,0 | | | |
| .79 | 20,0 | 8884 | SCBS-750 BLACK | .75 | 19,1 | 100 | 30,5 | 8891 |
| 1.02 | 26,0 | 8885 | SCBS-1000 BLACK | 1.00 | 25,4 | | | |
| 1.30 | 33,0 | 8886 | SCBS-1250 BLACK | 1.25 | 31,8 | 100 | 30,5 | 8892 |
| 1.57 | 40,0 | 8887 | SCBS-1500 BLACK | 1.50 | 38,1 | | | |
| 2.05 | 52,0 | 8888 | SCBS-2000 BLACK | 2.00 | 50,8 | 100 | 30,5 | * |

*No tool provided for the 2.00" bundle.



- Self-Closing Braided Sleeving (SCBS) can be used on pre-terminated wires due to the self closing concept. SCBS makes maintenance fast and effective. Simply open SCBS, make adjustments, and reinstall after service.
- The installation tool makes routing wire fast and easy.
- The 25% edge overlap allows coverage around inline connectors/plugs.
- Full cable flexibility is maintained in any direction, even at low temperatures. Wires encased in Heyco Self Closing Braided Sleeving can flex and bend as readily as if they had no protective oversleeving. Bundles can be flexed repeatedly without damage.
- Tough, cut-resistant sleeving is designed for protecting wire bundles and harnesses, hoses, tubing, and cable assemblies from mechanical damage and environmental hazards.
- Preferred cutting method: hot knife.

Heyco® Braided Sleeving

| BUNDLE RANGE | | | | PART NO. | | DESCRIPTION | PART DIMENSIONS | | | |
|------------------|------|------------------|------|-------------|-------------|-------------|------------------|------|--------------------|-----|
| Minimum Diameter | | Maximum Diameter | | Black | FR Black | | Nominal Diameter | | Quantity Per Spool | |
| in. | mm. | in. | mm. | | | in. | mm. | ft. | mtrs. | |
| .09 | 2,3 | .25 | 6,4 | 8980 | 8983 | BS 125 | .13 | 3,2 | 1000 | 305 |
| .13 | 3,2 | .44 | 11,1 | 8985 | 8988 | BS 250 | .25 | 6,4 | | |
| .25 | 6,4 | .75 | 19,1 | 8990 | 8993 | BS 500 | .50 | 12,7 | 500 | 152 |
| .50 | 12,7 | 1.25 | 31,8 | 8995 | 8998 | BS 750 | .75 | 19,1 | | |
| .75 | 19,1 | 1.75 | 44,5 | 9000 | 9003 | BS 1250 | 1.25 | 31,8 | 250 | 76 |
| 1.25 | 31,8 | 2.75 | 69,9 | 9005 | 9008 | BS 1750 | 1.75 | 44,5 | | |
| 1.50 | 38,1 | 3.50 | 88,9 | 9010 | 9013 | BS 2.0 | 2.00 | 50,8 | 200 | 61 |

Standard color black.

FR sleeving flammability rating-UL VW-1.



- Braided sleeve slips on quickly and is self-fitting over irregular shapes and contours. No wire pulling compounds are required due to its low surface friction. Slight tensioning after application makes for an even tighter fit.
- Expandable up to three times its own diameter, the open-weave construction can fit many applications, simplifying inventory. The open-weave allows for easy inspection of sleeved components and easy break out of individual cables.
- Full cable flexibility is maintained in any direction, even at low temperatures. Wires encased in Heyco Braided Sleeving can flex and bend as readily as if they had no protective oversleeving. Bundles can be flexed repeatedly without damage.
- Tough, cut-resistant sleeving is designed for protecting wire bundles and harnesses, hoses, tubing, and cable assemblies from mechanical damage and environmental hazards.
- Preferred cutting method: hot knife.

| SC Braided Sleeving | | Braided Sleeving | |
|---------------------|--------------------------------|-------------------|-----------------------------------------------------------------------------------|
| Material | Polyester | Materials | Polyester Monofilament Yarns or Flame Retardant Polyester Yarn |
| Flammability Rating | UL 94 V2 | Certifications | Recognized under the Component Program of Underwriters' Laboratories File E173954 |
| Temperature Range | -58°F (-50°C) to 302°F (150°C) | Monofilament Dia. | .010" |
| | | Temperature Range | -103°F (-75°C) to 257°F (125°C) |