

“Stay Connected” with



Power Components

a PennEngineering® Company

Now Available
in Single Reel
Order Quantities!




Heyco® Male Pins

For mating Female Pin & Connectors, see pages 8-47 thru 8-49


• DFARS Compliant

Dia. in.	PART DATA			PART NO.	APPLICATION TOOLING*				
	Overall Length in.	AWG Range	Material		Die**	Feeds	Tool Packs	Crimp Punch	Anvil
MP125 Series									
.125	.63	20-18	Brass	7062	7062UXX5	Left to Right	B300L/B301L	C229	C231
	.75	20-18	Brass	7060	7060UXX5				
	1.00	20-18	Brass	7064	7064UXX5	Left to Right	B304L/B305L	C230	C232
	.75	16-14	Brass	7068	7068UXX5				
MP141 Series									
.141	1.03	18-16	Brass	7171	7171UXX5	Left to Right	B340L/B341L	C135	C138
MP156 Series									
.156	1.03	18-16	Brass	7181	7181UXX5	Left to Right	B340L/B341L	C135	C138
	1.31	18-16	Brass	7180	7180UXX5				
MP178 Series									
.178	1.39	18-14	Brass	7194	7194UXX5	Right to Left	B360R/B361R	C001	C009
		12-10	Brass	7192	7192UXX5				

* Heyco high volume Application Tooling, designed for 3-5 ton presses - see page 8-59.
 Heyco Mini Applicators, designed for 1.5-3 ton bench top presses, are available - see page 8-59.
 ** “XX” represents Wire Gauge. Please specify Wire Gauge when ordering.




MP125 Series




NOTE: OPTIONAL CUT OFF ON ASSY. EQUIPMENT

MP141 Series



MP156 Series



MP178 Series

Materials

Alloy 260 Brass (70% Cu, 30% Zn. Higher Cu content resists dezincification)

Quick
Specs