



## Heyco® Original Strain Relief Bushings



### Right Angle for Round Cables

- Provides the same protection for your power supply cable as the straight-thru type AND...
- **Exits the cable flush against the panel**, saving space and directing the cable parallel to the panel.
- Overcomes space limitations and acts as a back or bottom bumper.
- See page 4-38 for corresponding **Mounting Hole Plugs** which can be used to fill blank/unused Mounting Holes and thus allow for a single panel design for multiple applications.
- Consult Heyco for other wire types and sizes.
- See pages 4-27 & 4-28 for SR assembly tools.
- For Double D Mounting Hole Punches, see page 4-30.

WILL FIT THESE CABLES				PANEL DIMENSIONS				PART		DESC.	PART DIMENSIONS				Mounting Hole Plug		
UL Type	AWG/ Conductors	Approximate Size		A Mounting Hole Dia.		B To Prevent Rotation		Finished Fit Panel Thickness*			NO. Black White	C HEAD LENGTH	D BODY LENGTH			PART NO.	
		in.	mm.	in.	mm.	in.	mm.	in.	mm.	in.			mm.	in.	mm.		
SV & SVT	18/2	.250	6,4	.500	12,7	.450	11,4	.100	2,5	1374	1375	SR 15-1	.39	9,9	.69	17,5	2491
	18/3	.265	6,7	.500-.515	12,7-13,1												
HPD	18/2	.270	6,9	.500	12,7	.660	16,8	.125	3,2	1397	1398	SR 17-2	.64	16,3	1,09	27,7	2503
	16/2	.290	7,4	.500-.515	12,7-13,1												
SJ, SJO & SJT	18/2	.300	7,6	.625	15,9	.550	14,0	.125	3,2	1320	1321	SR 10-2	.56	14,3	.97	24,6	2497
	16/2	.325	8,3														
	18/3	.330	8,4														
SJ	16/3	.330	8,4	.750	19,0	.660	16,8	.125	3,2	1397	1398	SR 17-2	.64	16,3	1,09	27,7	2503
SJ, SJO & SJT	16/2	.325	8,3														
	18/3	.330	8,4														
SJT	16/3	.335	9,0	.750-.781	19,0-19,8	.815	20,7	.125	3,2	1401	1402	SR 18-2	.84	21,4	1,36	34,5	2509
	18/4	.360	9,1														
SJT & SJTO	14/3	.370	9,4	.875	22,2	.815	20,7	.125	3,2	1401	1402	SR 18-2	.84	21,4	1,36	34,5	2509
SJ & ST	18/2	.390	9,9														
	18/3	.405	10,3														
	16/2	.405	10,3														
NEW! S	14/2	.530	13,5	.875	22,2	.815	20,7	.125	3,2	1401	1402	SR 18-2	.84	21,4	1,36	34,5	2509
	14/3	.560	14,2														

Standard color black. Consult Heyco for other colors.

\*Maximum Panel Thickness. Part has additional clearance. Consult Heyco for your Custom Finished Fit Panel Thickness.



Quick Specs

Material  
Certifications

Nylon 6/6

UL Recognized under the Component Program of Underwriters' Laboratories File E15331

CSA Certified by the Canadian Standards Association File 8919

Flammability Rating  
Temperature Range

94V-2

-04°F (-18°C) to 221°F (105°C)